

PRO OC8B-70V

8.0"/6.5" 2-Way 8ohm/70Volt, Indoor/Outdoor Dual Purpose, Loudspeaker

The dual purpose OC8B/OC65B 70V Indoor/Outdoor Constant Voltage Distribution speaker is the perfect choice for either main listening or sound reinforcement applications. It can be used in household applications or commercial distributed public address and sound systems. This ported bass reflex speaker supplies serious sound. It is provided with a switchable 8 ohm or 70Volt input with adjustable wattage taps.

The graphite mica mineral injected polypropylene woofer cone and butyl rubber surround are virtually impervious to the weather and insects. It delivers shock and awe. The 1" titanium tweeter presents clear crisp high frequencies to complement the hard driving bass.

The OC8B 70V can also be utilized as a stand alone subwoofer with or without an equalizer. In this function the OC8B 70V can be employed to launch deep bass into the listening area further enhancing the sound quality of your system.

This speaker color is offered is black. It can be painted to match any décor. The speaker enclosure is a durable UV-resistant material that allows for both indoor and outdoor installations. The perforated powdered coated aluminum alloy grill is long lasting, corrosion resistant, rust free and Coast Guard Approved.

Included in the package is a universal heavy gauge mounting kit. The kit includes a rust proof serrated U bracket and large easy to install positive locking knobs. The knobs are attached to the matching serrated area on the zero balanced point of the enclosure via threaded studs. This allows the speaker to easily be positioned to place the sound where you want it. Hand tightening the knobs will clamp the speaker in place. The speaker may be mounted either horizontally or vertically.

Electrical connection, up to 12 gauge wire, is made by gold plated constant tension spring loaded terminals via a 1/2" knock out terminal cover. An external switch allows selectable wattage taps of 60-30-15 or pass thru 8Ω.

One Hardwood Tree per pair is planted in the National Forest to offset the Styrofoam packaging. Current Audio is listed as a Green Manufacturer of products.

With our limited 5 year warranty you are assured years of superior trouble free operation.



SPECIFICATIONS

Driver	8" Mica Filled Polypropylene
Tweeter, 1" (25.4mm) Dome	Titanium
Frequency Response	42Hz-20kHz
Power Handling 8Ω	5-150 Watts @ 8Ω
Power Handling 70Volts	60-30-15 Watts @ 70Volts
SPL @ 1 Watt/1 meter	90 db
Impedance 8 ohm Nominal	Fixed Crossovers
Height X Width X Depth	16 1/2" (419mm) X 11" (279.4mm) X 10" (254mm)



Part Number	92089
Manual URL	www.currentaudio.com
Accessories	Volume Control ZL45R, ZL60S

