

OC65W

6.5" 2-Way Indoor/Outdoor, Cabinet Full Range Loudspeaker

The dual purpose OC65 Indoor/Outdoor speaker is the perfect choice for either main listening or sound reinforcement applications. Get ready for serious sound with this ported bass reflex speaker.

The 6.5" graphite mica filled polypropylene woofer cone and butyl rubber surround are virtually impervious to weather and insects. The 1" titanium tweeter delivers clear crisp high frequencies to provide high performance and high fidelity sound and it is the work horse of the line.

This speaker color is offered in both white and black. The white is a close match to Frazee White Shadow 181. It can be painted to match any décor. The speaker enclosure is a durable UV-resistant material that allows for both indoor and outdoor installations. The perforated powder-coated aluminum alloy grill is long-lasting, corrosion resistant and rust-free.

Included in the package is a universal heavy gauge mounting kit. The kit includes a rust proof U bracket and large easy to install positive locking serrated knobs. The knobs are attached to the matching serrated area on the zero balanced point of the enclosure via threaded studs. This allows the speaker to easily be positioned to place the sound where you want it. Hand tightening the knobs will clamp the speaker in place. The speaker may be mounted either horizontally or vertically.

Electrical connection, up to 12-gauge wire, is made by gold plated constant tension spring loaded terminals.

This speaker is also offered in a Pro 70Volt version with various wattage taps and a 1/2" knock out terminal cover.

With our limited lifetime warranty, you are assured years of superior trouble free operation.

Part Number	92039
Manual URL	www.currentaudio.com
Accessories	- Volume Control



SPECIFICATIONS

Driver	6.5" Mica Filled Polypropylene Cone with Butyl Rubber Surround
Tweeter	1" (25mm) Titanium Dome
Grill specification	Perforated aluminum
Frequency Response	47Hz – 20kHz
Impedance (nominal)	8 ohms
Power Handling	5 – 125 Watts
SPL	90 dB 1W/1m
Length x Width x Depth	12 1/8" (308mm) x 8 1/2" (216mm) x 7 7/8" (200mm)
Standard Pair Pack Dimensions (weight)	18 3/4" x 11 1/4" x 14 3/4" (16 lbs.)
Master Pack Dimensions 2 pair (weight)	22 1/2" x 19 1/4" x 16" (36 lbs.)

