

# OC8B

## 8.0" 2-Way Indoor/Outdoor, Dual Purpose, Full Range Loudspeaker

The dual purpose OC-8 Indoor/Outdoor speaker is the perfect choice for either main listening or sound reinforcement applications. This ported bass reflex speaker supplies serious sound.

The 8" graphite mica filled polypropylene woofer cone and butyl rubber surround are virtually impervious to the weather and insects. It delivers shock and awe. The 1" titanium tweeter presents clear crisp high frequencies to complement the hard driving bass.

The OC8 can also be utilized as a stand alone subwoofer with or without an equalizer. In this function the OC-8 can be employed to launch deep bass into the room further enhancing the sound quality of your system.

This speaker color is offered in black. It can be painted to match any décor. The speaker enclosure is a durable UV-resistant material that allows for both indoor and outdoor installations. The perforated powder-coated aluminum alloy grill is long-lasting, corrosion resistant and rust-free.

Included in the package is a universal heavy gauge mounting kit. The kit includes a rust proof U bracket and large easy to install positive locking serrated knobs. The knobs are attached to the matching serrated area on the zero balanced point of the enclosure via threaded studs. This allows the speaker to easily be positioned to place the sound where you want it. Hand tightening the knobs will clamp the speaker in place. The speaker may be mounted either horizontally or vertically.

Electrical connection, up to 12-gauge wire, is made by gold plated constant tension spring loaded terminals.

This speaker is also available in a 70 volt version with various wattage taps and a 1/2" knock out terminal cover.

One hardwood tree is planted in the National Forest to offset the styrofoam packaging on each pair.

With our limited lifetime warranty, you are assured years of superior trouble free operation.

Part Number	92038
Manual URL	<a href="http://www.currentaudio.com">www.currentaudio.com</a>
Accessories	- Volume Control, ZL45RW



### SPECIFICATIONS

Driver	8.0" Mica Filled Polypropylene Cone
Tweeter	1" (25mm) Titanium Dome
Crossover	Gold press terminals
Grill specification	Perforated aluminum
Frequency Response	42Hz – 20kHz
Impedance (nominal)	8 ohms
Power Handling	5 – 150 Watts
SPL	90 dB 1W/1m
Length x Width x Depth	16 1/2" (419mm) x 11 3/8" (289mm) x 10 1/4" (260mm)
Standard Pair Pack Dimensions (weight)	22" x 14" x 19" (32 lbs.)

